#### LISTING OF THE CLAIMS

The listing of claims will replace all prior versions, and listings of claims in the application:

### 1. (Currently Amended) A cabinet comprising:

a first side wall:

a first support member punched out of and extending from the first side wall such that a first opening is formed through the first side wall adjacent the first support member, wherein the first support member includes a straight first leg extending perpendicular to the first side wall and a straight second leg extending perpendicular from the first leg spaced from and substantially parallel to the first side wall, the second leg includes a hemispherical dimple with rounded edges punched in a straight portion of the second leg, wherein said dimple extends toward said first opening;

a second side wall positioned opposite the first side wall;

a third wall interconnecting the first and second side walls;

a base wall interconnecting the first, second and third walls, and

a second support member punched out of and extending from the third wall such that a second opening is formed through the third wall adjacent the second support member, the second support member is positioned at substantially the same height from the base wall as the first support member on the first wall, the second support member includes a straight first leg extending perpendicular to the third wall and a straight second leg extending perpendicular from the first leg spaced from and at least substantially parallel to the third wall, the second leg of the second support member includes a hemispherical dimple with rounded edges formed in a straight portion of the second leg, wherein said dimple extends toward said second opening; and

a removable shelf including a planar surface and a first flange depending from the planar surface, the first flange includes [[an]]a circular opening extending completely therethrough dimensioned to receive the rounded edges of said dimple of the first support member on the first side wall when the first flange is received between the

second leg of the first support member and the first side wall, and the shelf includes a second flange depending from the planar surface, the second flange includes [[an]]a circular opening extending completely therethrough dimensioned to receive the rounded edges of the dimple of the second support member when the second flange is received between the second leg of the second support member and the third wall;

a third support member punched out of and extending from the third wall such that a third opening is formed through the third wall adjacent the third support member, the third support member includes a straight first leg extending perpendicular to the third wall and a straight second leg extending perpendicular from the first leg spaced from and substantially parallel to the third wall, the second straight leg of the third support member includes a substantially-hemispherical dimple having rounded edges extending towards an inner surface of the third side wall, and the removable shelf further including a third flange depending from [[a]]the planar surface, the third flange includes a circular opening extending completely therethrough that receives the rounded edges of the dimple of the third support member on the third side wall when the third flange is received between the second leg of the third support member and the third wall.

### 2-4. (Cancelled).

- (Currently Amended) The cabinet of claim 1, wherein the first, second and third support members each has-have a rounded upper edge.
- (Previously Presented) The cabinet of claim 1, wherein each of said first, second and third members is a lance.

# 7-8. (Cancelled).

 (Original) The cabinet of claim 1, wherein said cabinet is fabricated from metal.

## 10.-13. (Cancelled).

14. (Previously Presented) The cabinet of claim 1, further comprising a support wall disposed between the first side wall and the second side wall in a first direction and the removable shelf and the base wall in a second direction.

15.-21. (Cancelled)